

Monomanual I/A System single-use (coaxial)

- Lightweight monomanual irrigation / aspiration handpiece
- Compatible with Phaco or I/A System via standard Luer connectors
- Smooth abrasive (rough) tip available for capsule polishing
- Angled tip: 45° or 65° available
- Swiss Design / Swiss Made

Tip variants



Monomanual I/A System single-use, angled 45°

Art. No.	Description
CX2045-P	Monomanual I/A System single-use 20G (Ø0.90mm), polished tip, angled 45°, asp. port Ø0.35mm, incl. silicone sleeve 16G (Ø1.70mm) for irrigation with dual-side ports Ø1.10mm
CX2045-R	Monomanual I/A System single-use 20G (Ø0.90mm), rough tip, angled 45°, asp. port Ø0.35mm, incl. silicone sleeve 16G (Ø1.70mm) for irrigation with dual-side ports Ø1.10mm
CX2145-P	Monomanual I/A System single-use 21G (Ø0.80mm), polished tip, angled 45°, asp. port Ø0.35mm, incl. silicone sleeve 17G (Ø1.50mm) for irrigation with dual-side ports 1.65x0.77mm
CX2145-R	Monomanual I/A System single-use 21G (Ø0.80mm), rough tip, angled 45°, asp. port Ø0.35mm, incl. silicone sleeve 17G (Ø1.50mm) for irrigation with dual-side ports 1.65x0.77mm
CX2245-P	Monomanual I/A System single-use 22G (Ø0.70mm), polished tip, angled 45°, asp. port Ø0.35mm, incl. silicone sleeve 18G (Ø1.40mm) for irrigation with dual-side ports 1.50x0.67mm
CX2245-R	Monomanual I/A System single-use 22G (Ø0.70mm), rough tip, angled 45°, asp. port Ø0.35mm, incl. silicone sleeve 18G (Ø1.40mm) for irrigation with dual-side ports 1.50x0.67mm

Monomanual I/A System single-use, angled 65°

Art. No.	Description
CX2065-P	Monomanual I/A System single-use 20G (Ø0.90mm), polished tip, angled 65°, asp. port Ø0.35mm, incl. silicone sleeve 16G (Ø1.70mm) for irrigation with dual-side ports Ø1.10mm
CX2065-R	Monomanual I/A System single-use 20G (Ø0.90mm), rough tip, angled 65°, asp. port Ø0.35mm, incl. silicone sleeve 16G (Ø1.70mm) for irrigation with dual-side ports Ø1.10mm
CX2165-P	Monomanual I/A System single-use 21G (Ø0.80mm), polished tip, angled 65°, asp. port Ø0.35mm, incl. silicone sleeve 17G (Ø1.50mm) for irrigation with dual-side ports 1.65x0.77mm
CX2165-R	Monomanual I/A System single-use 21G (Ø0.80mm), rough tip, angled 65°, asp. port Ø0.35mm, incl. silicone sleeve 17G (Ø1.50mm) for irrigation with dual-side ports 1.65x0.77mm

